

LED 3528 Strip Series



PSLB3528Y(N)-X-30(60/120)

LED by **EVERLIGHT**

■ Features 產品特色

- Supply Voltage : 12V DC
輸入電壓 : 12V DC
- No UV and radiation.
無紫外線及紅外線。
- Long life. (up to 40,000 hours at ambient temp. 25°C)
產品壽命長，工作於 25 度環境下可達 4 萬小時。
- Able to be used in office, home, building construction or decoration illumination...and so on.
適用於家用及商用空間...等。
- Warranty : 1 year
產品保固 : 1 年。
- We can follow customer's requirement, such as, size, Length to manufacture.
可依客戶需求尺寸訂製。

■ Specifications 產品基本規格

Item	規格項目	規格內容 Spec.
LED pcs/m	1 米 LED 數量	30pcs/m 60pcs/m 120pcs/m
Input Voltage	輸入電壓	12V DC
LED Color	LED 發光色	(W 白光) 6,000~6,500K
		(M 暖白) 2,700~3,200K
		(R 紅光) 625nm
		(Y 黃光) 590nm
		(B 藍光) 470nm
(G 綠光) 525nm		
Products IP Type	產品防水樣式	(裸板)None IP / (矽膠套管) IP65 / (矽膠套管填膠) IP68
Power Consumption	總消耗功率	30pcs/m→2.1W 60pcs/m→4.2W 120pcs/m→8.4W
Illumination Angle	發光角度	120°
Operating Temperature	工作溫度	-30°C ~+45°C
Storage Temperature	儲存溫度	-40°C ~+80°C
Lifetime (System)	產品壽命	>30,000 hr

■ LED 3528 Strip

